Attenuator

Attenuator, 2.92mm 2Watt 20dB 40GHz

P.N.: F17-B4020-02

Products feature

- Reliable V.S.W.R. and Attenuation
- Wide broadband frequency application from Telecommunication to Microwave
- Directional 2 Watt rating



Electrical specification

| ltem | Specification |
|---------------------|--------------------------------------|
| Frequency Range | DC ~ 40 GHz |
| Impedance (Nominal) | 50Ω |
| Power Rating | 2 Watt |
| Attenuation | 20 dB - 1.0/+1.5 dB/max |
| V.S.W.R (max) | 1.35 : 1 |
| Connector Type | 2.92 male(Input) – female(Output) |

Material specification

| ItemSpecificationConnectorStainless Steel PassivatedBodyStainless Steel PassivatedWeight5 GramDimension31mm * Ø 8.0 | | The second |
|---|-----------|---|
| ConnectorPassivatedBodyStainless Steel PassivatedWeight5 Gram | ltem | Specification |
| Body Passivated Weight 5 Gram | Connector | |
| | Body | |
| Dimension 31mm * Ø 8.0 | Weight | 5 Gram |
| | Dimension | 31mm * Ø 8.0 |

Tel : (+82)2- 866 -9003 Fax : (+82)2-6280-9333 www.srtechnology.com sale@srtechnology.com